

## Connecting Link X-015 Grade 10

---

### Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Suitable for use with both Grade 8 and Grade 10 chain.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL  
... [Read more](#)

---

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, Type, manufacturer ID, traceability.

**Temperature range:** -40° up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-1


**Safety factor:** 4:1

**Grade:** 10

**Australian Standard:** AS 3776

## Connecting Link X-015 Grade 10

### Blueprint



### Technical data

| Part Code    | Chain size mm | WLL ton | EWL mm | A mm | B mm | D mm | K mm | Weight (kg) |
|--------------|---------------|---------|--------|------|------|------|------|-------------|
| 402200140190 | 6             | 1.4     | 45     | 15   | 17   | 7    | 45   | 0.08        |
| 402200250190 | 7-8           | 2.5     | 59     | 18   | 23   | 9    | 59   | 0.2         |
| 402200400190 | 10            | 4       | 69     | 25   | 27   | 11   | 69   | 0.3         |
| 402200670190 | 13            | 6.7     | 92     | 30   | 37   | 16   | 92   | 0.7         |
| 402201000190 | 16            | 10      | 101    | 36   | 39   | 19   | 101  | 1.2         |
| 402201600190 | 20            | 16      | 122    | 42   | 46   | 23   | 122  | 2.1         |
| 402201900190 | 22            | 19      | 152    | 49   | 59   | 24   | 152  | 3.5         |
| 402202650190 | 26            | 26.5    | 162    | 55   | 62   | 30   | 162  | 4.8         |
| 402204000190 | 32            | 40      | 203    | 69   | 79   | 36   | 203  | 9           |