



## Connecting Link X-015 Grade 10

### Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Suitable for use with both Grade 8 and Grade 10 chain.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, Type, manufacturer ID, traceability.

**Temperature range:** -40° up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-1

**Safety factor:** 4:1

**Grade:** 10

**Australian Standard:** AS 3776

| Part Code    | Chain size mm | WLL ton | EWL mm | Amm mm | Bmm mm | Dmm mm | Kmm mm | Weight (kg) |
|--------------|---------------|---------|--------|--------|--------|--------|--------|-------------|
| 402200140190 | 6             | 1.4     | 45     | 15     | 17     | 7      | 45     | 0.08        |
| 402200250190 | 7-8           | 2.5     | 59     | 18     | 23     | 9      | 59     | 0.2         |
| 402200400190 | 10            | 4       | 69     | 25     | 27     | 11     | 69     | 0.3         |
| 402200670190 | 13            | 6.7     | 92     | 30     | 37     | 16     | 92     | 0.7         |
| 402201000190 | 16            | 10      | 101    | 36     | 39     | 19     | 101    | 1.2         |
| 402201600190 | 20            | 16      | 122    | 42     | 46     | 23     | 122    | 2.1         |
| 402201900190 | 22            | 19      | 152    | 49     | 59     | 24     | 152    | 3.5         |
| 402202650190 | 26            | 26.5    | 162    | 55     | 62     | 30     | 162    | 4.8         |
| 402204000190 | 32            | 40      | 203    | 69     | 79     | 36     | 203    | 9           |

## Blueprint

