



Connecting link X-015 Grade 10

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Suitable for use with both Grade 8 and Grade 10 chain.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-1

Australian Standard: AS 3776

Safety factor: 4:1

Grade: 10

Australian Standard: AS 3776

Part Code	Chain size mm	WLL ton	A mm	B mm	D mm	K mm	Weight (kg)
402200140190	6	1.4	15	17	7	45	0.08
402200250190	7-8	2.5	18	23	9	59	0.2
402200400190	10	4	25	27	11	69	0.3
402200670190	13	6.7	30	37	16	92	0.7
402201000190	16	10	36	39	19	101	1.2
402201600190	20	16	42	46	23	122	2.1
402201900190	22	19	49	59	24	152	3.5
402202650190	26	26.5	55	62	30	162	4.8
402204000190	32	40	69	79	36	203	9

Blueprint

