

## **Lever Hoist KITO LX Series**

## **Product information**

The KITO LX Series is a range of small lever hoists that is suitable for operations in limited space. The lever hoist has a freewheel safeguard and the bottom hook is riveted in four places. Its solid aluminium housing enables a low weight of the hoist. The load can be lifted or lowered in 2 mm steps due to its smooth gear mechanism.

Material: High impact aluminium housing, nickel-plated load chain in grade 10.

Marking: CE-marked, Type plate with WLL, CE-marking and serial number.

Finish: Surface treated aluminium.

Safety factor: 4:1.

Australian Standard: AS 1418.2

Part Code	Code	WLL ton	Lifting height m	Hand pull to lift full load daN	Load chain Ø mm	Chain falls	A mm	B mm	C mm	D mm	e mm	g mm	t mm	s mm	Weight (kg)
500500030150040	LX003	0.25	1.5	20	3,2 x 9,0	1	90,5	73,5	205	150	62	21,0	11	32	1.7
500500030200040	-	0.25	2	20	3,2 x 9,0	1	-	-	-	-	-	-	-	-	1.8
500500030300040	-	0.25	3	20	3,2 x 9,0	1	-	-	-	-	-	-	-	-	2
500500050150040	LX005	0.5	1.5	31	4,3 x 12,0	1	102,0	93,0	246	180	68	24,5	12	35,5	2.7
500500050300040	-	0.5	3	31	4,3 x 12,0	1	-	-	-	-	-	-	-	-	3.3

## Blueprint

