



Lever Hoist KITO LX Series

Product information

The KITO LX Series is a range of small lever hoists that is suitable for operations in limited space. The lever hoist has a freewheel safeguard and the bottom hook is riveted in four places. Its solid aluminium housing enables a low weight of the hoist. The load can be lifted or lowered in 2 mm steps due to its smooth gear mechanism.

Material: High impact aluminium housing, nickel-plated load chain in grade 10.

Marking: CE-marked, Type plate with WLL, CE-marking and serial number.

Finish: Surface treated aluminium.

Safety factor: 4:1.

Australian Standard: AS 1418.2

Part Code	Code	WLL ton	Lifting height m	Number of falls	Load chain mm	a mm	b mm	C*	D mm	e mm	Weight (kg)
500500030150040	LX003S015	0.25	1.5	1	3.2 x 9.0	90.5	73.5	205	150	62	1.7
500500030200040	LX003S020	0.25	2	1	3.2 x 9.0	90.5	73.5	205	150	62	1.8
500500030300040	LX003S030	0.25	3	1	3.2 x 9.0	90.5	73.5	205	150	62	2
500500050150040	LX005S015	0.5	1.5	1	4.3 x 12.0	102	93	246	180	68	2.7
500500050300040	LX005S030	0.5	3	1	4.3 x 12.0	102	93	246	180	68	3.3

Blueprint

