



## Manual Chain Hoist KITO CX Series

### Product information

The KITO chain block CX has a light-weight aluminium housing, and is the size of a coaster. The hooks are suitable for a larger intake and its compact measures enables maximum lifting height. Flush-mounted screws at the housing reduce the injury risk. The standard chain block is equipped with an overload protection.

**Material:** High impact aluminium housing, nickel-plated load chain in grade 10.

**Marking:** Type plate with WLL, CE-marking and serial number.

**Finish:** Surface treated aluminium.

**Safety factor:** 4:1

**Australian Standard:** AS 1418.2

| Part Code       | Code  | WLL ton | Lifting height m | Number of falls | Load chain mm | Hand force max. kg | Hand chain length m | Weight (kg) |
|-----------------|-------|---------|------------------|-----------------|---------------|--------------------|---------------------|-------------|
| 500100030250300 | CX003 | 0.25    | 2.5              | 1               | 3,2 x 9,0     | 14,7               | -                   | 2.2         |
| 500100030300300 | CX003 | 0.25    | 3                | 1               | 3,2 x 9,0     | 14,7               | -                   | 2.4         |
| 500100050250300 | CX005 | 0.5     | 2.5              | 1               | 4,3 x 12,1    | 18,6               | -                   | 4.05        |
| 500100050300300 | CX005 | 0.5     | 3                | 1               | 4,3 x 12,1    | 18,6               | 6                   | 4.5         |

## Blueprint

