

Clevis Sling Hook X-043/S Grade 10

Product information



At least 25% greater WLL than traditional Grade 8 products.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Tempering temperature minimum 400°C.
Magnaflux crack detection is performed 100% on each batch.

... [Read more](#)

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard, Size, grade, manufacturer ID, traceability.
Temperature range: -40°C up to +200°C (without reduction in WLL).
Finish: Blue painted.
Standard: EN 1677-2


Safety factor: 4:1

Grade: 10

Australian Standard: AS 3776

Clevis Sling Hook X-043/S Grade 10

Blueprint



Technical data

Part Code	Chain size mm	WLL ton	EWL mm	A mm	H mm	K mm	P1 mm mm	T mm	Weight (kg)
402300140700	6	1.4	79	7	18	79	23	15	0.3
402300250700	7-8	2.5	98	9	22	98	27	18	0.6
402300400700	10	4	122	12	30	122	34	24	1.1
402300670700	13	6.7	147	15	37	147	44	30	2.3
402301000700	16	10	166	17	41	166	48	39	3.8
402301600700	20	16	207	24	64	207	57	48	8.7
402301900700	22	19	217	25	61	217	73	52	9.5