



## Alloy Swivel Bearing Hoist Hook 8-175N

### Product information

Built with ball bearing and enables full swivel feature under load. At least 25% greater WLL than traditional Grade 8 products. Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL. Magnaflux crack detection is performed 100% on each batch.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard

**Temperature range:** Tempering temperature minimum 400°C

**Standard:** EN 1677-1

*Australian Standard: AS 3776*

**Safety factor:** 4:1

**Grade:** 10

**Australian Standard:** AS 3776

| Part Code    | Chain size<br>mm | WLL<br>ton | Type | A<br>mm | B<br>mm | C<br>mm | D<br>mm | G<br>mm | H<br>mm | K<br>mm | L<br>mm | P<br>mm | P1<br>mm | T<br>mm | Weight<br>(kg) |
|--------------|------------------|------------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|----------|---------|----------------|
| 420500200660 | 7-8              | 2          | CC   | 36      | 29      | 26      | 13      | 91      | 25      | 143     | 181     | 24      | 20       | 22      | 0.9            |

## Blueprint

