



Swivel Self Locking Hook X-027N

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Rotate when loaded.
- Proof load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- Built with ball bearing and enables full swivel feature under load.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard

Temperature range: Tempering temperature minimum 400°C .

Finish: Blue painted.

Standard: EN 1677-3

Safety factor: 4:1

Grade: 10

Australian Standard: AS 3776

Part Code	Chain size mm	WLL ton	A mm	B mm	D mm	H mm	K mm	P mm	T mm	Weight (kg)
420500140950	6	1.4	32	23	12	19	149	28	15	0.7
420500250950	7-8	2.5	36	29	13	24	186	34	20	1.2
420500400950	10	4	41	35	16	30	218	44	26	2
420500670950	13	6.7	46	44	21	39	276	51	30	4.1
420501000950	16	10	61	50	23	49	329	60	36	7.2
420501600950	20	16	74	82	25	65	403	70	53	13
420501900950	22	19	97	96	33	63	454	80	49	20
420502650950	26	26.5	123	116	51	69	535	99	56	33

Blueprint

