Lifting Solutions Group
Axel Johnson International

RUD VLBS Lifting Point

Product information



- Suspension ring pivots 180°
- Suspension ring & weld-on-block of the VLBS-U are undetachable
- Suspension ring can be angled into position (VLBS-U)

Available in with and without spring versions.

... *Read more*

Material: Forged of high strength steel.
Marking: CE-marked, WLL, indication for the most unfavourable case.
Finish: Striking fluorescent pink powder coating.

Safety factor: 4:1.


Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

RUD VLBS Lifting Point

Blueprint



Technical data

Part Code	Code	WLL ton	Eye diameter mm	T mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight (kg)
42157993115	VLBS-1,5t without spring	1.5	25	65	33	66	25	38	40	14	33	14	0.35
42157995346	VLBS-2,5t without spring	2.5	27	75	38	77	28	45	47	16	40	16	0.53
42157993116	VLBS-4t without spring	4	32	83	42	87	31	51	52	18	46	16	0.72
42157993117	VLBS-6,7t without spring	6.7	44	117	61	115	44	67	73	24	60	22.5	1.89
42157993118	VLBS-10t without spring	10	55	126	75	129	55	67	71	26.5	60	26.5	2.75
42157993041	VLBS-16t without spring	16	69	176	96	192	70	100	106	40	90	26	7.1

© November 2026 - All Rights Reserved