

## RUD VRM STARPOINT Eye Nut

### Product information



Multi-directional threaded design, load rating up to six times the capacity of collared eye nuts.

Design: Octagonal lifting eye.

For bolts with min. quality class 10.9

... [Read more](#)

**Material:** Forged high strength steel

**Marking:** According to standard, CE-marked, WLL, indication for the most unfavourable case

**Temperature range:** -40° up to 100°C (no reduction of WLL)

**Finish:** Striking fluorescent pink powder coating


**Standard:** EN 1677-1

**Safety factor:** 4:1

**Grade:** 10

## RUD VRM STARPOINT Eye Nut

### Blueprint



### Technical data

Part Code	Code	Diameter mm	WLL ton	Thread	B mm	Cmm mm	Dmm mm	Emm mm	Fmm mm	Gmm mm	Hmm mm	lmm mm	Kmm mm	Lmm mm	Nmm mm	Tmm mm	Weight (kg)
421100010272	VRM	-	0.1	M6	9	7	20	23	16	28	17	13	37	11	9	28	0.06
421100030270	VRM	25	0.3	M8	11	9	25	25	21	30	21	16.3	47	14	12	35	0.1
421100040270	VRM	25	0.4	M10	11	9	25	25	21	30	21	16.3	47	14	12	35	0.1
421107500270	VRM	30	0.75	M12	13	10	30	30	24	34	25	19.8	56	17	14	42	0.18
421100150270	VRM	35	1.5	M16	15	13	35	36	30	40	29	23.6	65	21	19	49	0.32
421100230270	VRM	40	2.3	M20	17	16	40	41	37	50	35	29.3	76	23	24	58	0.48
421100320270	VRM	48	3.2	M24	20	19	49	51	45	60	41	35.2	92	29	30	70	0.83
421100450270	VRM	60	4.5	M30	26	24	60	66	56	75	51	44	114	36	36	87	1.32