Lifting Solutions Group
Axel Johnson International

RUD RS-M Lifting Eye Bolt

Product information



Octagonal lifting eye approved for lifting. Rate for use in both single and multi-part lifts.

... *Read more*

Material: Forged of high strength steel.
Marking: According to standard, CE-marked, WLL, indication for the most unfavourable case
Temperature range: -40°C up to 200°C
Standard: EN 1677-1

Safety factor: 4:1
Grade: 8

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

RUD RS-M Lifting Eye Bolt

Blueprint



Technical data

Part Code	Code	WLL ton	Thread	Eye diameter mm	A mm	B mm	C mm	D mm	E mm	T mm	Weight (kg)
421100010252	RS-M6	0.1	M6	25	12	11	10	25	25	34	0.1
421100020250	RS-M8	0.2	M8	25	12	11	10	25	25	34	0.1
421100030250	RS-M10	0.25	M10	25	15	11	10	25	25	34	0.1
421100040250	RS-M12	0.4	M12	30	18	13	12	30	30	41	0.18
421100080250	RS-M14	0.75	M14	35	21	15	14	35	35	48	0.29
421100100250	RS-M16	1	M16	35	24	15	14	35	35	48	0.3
421100120250	RS-M18	1.2	M18	40	30	17	16	40	40	55	0.45
421100150250	RS-M20	1.5	M20	40	30	17	16	40	40	55	0.47
421100200250	RS-M24	2	M24	50	36	21	20	50	50	70	0.89
421100300250	RS-M30	3	M30	60	45	26	24	60	60	85	1.62
421100400250	RS-M36	4	M36	90	54	43	38	90	100	130	6.5
421100600250	RS-M42	6	M42	90	63	43	38	90	100	130	6.5
421100800250	RS-M48	8	M48	90	67	43	38	90	100	130	6.5

© November 2026 - All Rights Reserved