

RUD VRBS Lifting Ring

Product information

Load ring for plane surfaces. 180° pivoting.

Marking: According to standard, CE-marked

Temperature range: -20°C to +200°C.

Finish: Pink powder coated.











Standard: EN 1677-1

Safety factor: 4:1



Part Code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	T mm	Weight (kg)
42157992488	4	62	14	28	48	135	71	65	0.77
42157992489	6.7	88	20	39	60	170	92	84	1.64
42157992490	10	100	22	46	65	195	100	95	2.62
42157992491	16	130	30	57	90	263	134	127	5.53
421560267	31.5	160	42	78	130	373	195	178	15.6

Technical data

Method of lift										
Number of legs	1	1	2	2	2	2	2	3 / 4	3 / 4	3 / 4
Angle of inclination β	0°	90°	0°	90°	0-45°	>45-60°	Un-symm.	0-45°	>45-60°	Un-symm.
Factor	1	1	2	2	1.4	1	1	2.1	1.5	1
Type	For the max. total load weight >G< in metric tons									
VRBS 4 t	4 t	4 t	8 t	8 t	5.6 t	4 t	4 t	8.4 t	6 t	4 t
VRBS 6.7 t	6.7 t	6.7 t	13.4 t	13.4 t	9.4 t	6.7 t	6.7 t	14.1 t	10 t	6.7 t
VRBS 10 t	10 t	10 t	20 t	20 t	14 t	10 t	10 t	21.2 t	15 t	10 t
VRBS 16 t	16 t	16 t	32 t	32 t	22.4 t	16 t	16 t	33.6 t	24 t	16 t
VRBS 31.5 t	31.5 t	31.5 t	63 t	63 t	45 t	31.5 t	31.5 t	67 t	47.5 t	31.5 t
VRBS 50 t	50 t	50 t	100 t	100 t	70 t	50 t	50 t	105 t	75 t	50 t

Blueprint

