Lifting Solutions Group
Axel Johnson International

RUD VRBK-FIX Lifting Ring

Product information

Load ring for edge attachments. Welded on the corner reduces the number of lifting points. Loadable in any direction. Low profile and 270º pivoting.

... *Read more*



Material: CrNiMo Steel
Marking: According to standard
Temperature range: -20° to +200°C.
Finish: Pink powder coated.
Standard: EN 1677-1

Safety factor: 4:1.

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

RUD VRBK-FIX Lifting Ring

Blueprint



Technical data

Part Code	Code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	T mm	Weight (kg)
42157902149	VRBK-FIX 4 t	4	32	14	28	48	141	30	65	1
42157902150	VRBK-FIX 6.7 t	6.7	40	20	35	60	181	34	84	2.16
42157902256	VRBK-FIX 10 t	10	52	22	46	65	212	46	94	4.4
42157904653	VRBK-50 t	50	134	70	118	230	626	96	303	76.35

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved