Lifting Solutions Group
Axel Johnson International

Swivel Hook Crosby L-322 CN.

Product information



Features:

- Suitable for positioning of the hook before the load is lifted.
- Swivel hooks are load rated.
- Proper design, careful forging, and precision controlled quench and tempering gives maximum strength without excessive weight and bulk.

Hoist hooks incorporate markings forged into the product which address two (2) QUIC-CHECK® features:

- Deformation Indicators -- Two strategically placed marks, one just below the shank or eye and the other on the hook tip, which allows for a QUIC-CHECK® measurement to determine if the throat opening has changed, thus indicating abuse or overload.
- Angle Indicators — Indicates the maximum included angle which is allowed between two (2) sling legs in the hook. These indicators also provide the opportunity to approximate other included angles between two sling legs

... Read more

Material: Carbon steel - Forged, Quenched & Tempered.
Marking: CE-marked
Note: This hook is a positioning device and is not intended to rotate under load.

Safety factor: 5:1
Grade: 4

Australian Standard: AS 3776


Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Swivel Hook Crosby L-322 CN.

Blueprint



Technical data

Part Code	WLL ton	A mm	B mm	C mm	D mm	F mm	G mm	H mm	J mm	K mm	L mm	M mm	O*mm mm	R mm	S mm	AA**mm mm	Weight (kg)
420500080280	0.75	51	20.8	31.8	72.5	31.8	18.5	20.6	23.6	16	144	16	23.6	116	9.65	38.1	0.34
420500100280	1	63.5	33.3	38.1	80	35.1	21.3	23.9	24.6	18	170	18	24.6	136	12.7	50.8	0.57
420500160280	1.6	76	38.1	44.5	91	38.1	25.4	29.5	26.9	22.4	197	22.4	26.9	155	16	50.8	1.02
420500200280	2	76	38.1	44.5	102	41.1	28.7	33.3	30.2	23.9	210	23.9	29.5	165	16	50.8	1.04
420500320280	3.2	89	41.7	50.8	123	51	36.6	41.4	38.1	33.3	246	28.7	35.8	191	19.1	63.5	2.25
420500500280	5	116	58	63.5	160	63.5	46	52.5	45.2	42.2	317	36.6	42.9	245	25.4	76.2	4.67
420500750280	7.5	127	62	70	192	76	57	67	51	47.8	375	41.4	56.5	289	28.7	101	8.8
420501000280	10	143	63	79	212	82.5	66	74.5	66.5	55.5	417	49.3	61	311	31.8	101	10.5
420501500280	15	180	95.5	104	263	108	76	89	86.5	68.5	542	60.5	81	424	38.1	127	21.3

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved