Lifting Solutions Group
Axel Johnson International

Dee Shackle with Safety Pin

Product information



Dee shackle with safety pin.

- Manufactured and tested in accordance with AS2741.
- All bodies are marked with the batch number for traceability.
- All parts are hot dip galvanized for long life.
- Test and mill certificates available on request.

... *Read more*

Material: Forged alloy steel
Marking: CE-marked
Temperature range: -10°C up to +200°C
Finish: Hot dip Galvanised with blue painted pins


Safety factor: 6:1
Grade: 6

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Dee Shackle with Safety Pin

Blueprint



Technical data

Part Code	WLL ton	d mm	D mm	W mm	L mm	E mm	Weight (kg)
420100331180	3.25	16	9	27	51	40	0.6
420100651180	6.5	22	25	37	71	54	1.5
420100851180	8.5	25	29	43	81	60	2.3
420100951180	9.5	29	32	46	90	67	3.3
420101701180	17	38	41	60	124	92	7.7
420103501180	35	51	57	83	171	127	18.8
420105501180	55	63	70	105	203	152	35

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved