



Sling Hook EKN with Latch

Product information

Sling hook with latch.

Material: Quenched and tempered alloy steel.

Marking: According to standard, code and grade.

Finish: Painted.

Standard: EN 1677

Warning: Not to be heat treated.

Safety factor: 4:1

Grade: 10

Australian Standard: AS 3776

| Part Code | Code | WLL ton | B mm | E mm | F mm | G mm | H mm | L mm | Weight (kg) |
|--------------|------------|------------|---------|---------|---------|---------|---------|---------|----------------|
| 402300150180 | EKN-6-10 | 1.5 | 25 | 23 | 10 | 17 | 20 | 93 | 0.4 |
| 402300260180 | EKN-7/8-10 | 2.6 | 26 | 28 | 12 | 17 | 23 | 108 | 0.6 |
| 402300400180 | EKN-10-10 | 4 | 37 | 34 | 14 | 23 | 30 | 134 | 1 |
| 402300680180 | EKN-13-10 | 6.8 | 42 | 44 | 18 | 28 | 38 | 166 | 2.1 |
| 402301030180 | EKN-16-10 | 10.3 | 53 | 56 | 22 | 36 | 47 | 203 | 4 |
| 402301600180 | EKN-20-10 | 16 | 60 | 61 | 26 | 42 | 60 | 229 | 6.4 |
| 402302000180 | EKN-22-10 | 20 | 73 | 64 | 31 | 43 | 67 | 267 | 8.9 |
| 402302730180 | EKN-26-10 | 27.3 | 82 | 66 | 32 | 51 | 75 | 301 | 13 |
| 402304000180 | EKN-32-10 | 40 | 96 | 90 | 38 | 61 | 98 | 353 | 25 |

Blueprint

