Lifting Solutions Group
Axel Johnson International

Grab Hook OG

Product information



Eye shortening hook. No reduction of working load limit, thanks to supporting lugs on either side of hook to prevent chain link deformation.

... *Read more*

Material: Quenched and tempered alloy steel.
Marking: According to standard, code and grade.
Finish: Painted.
Standard: EN 1677
Warning: Not to be heat treated.

Safety factor: 4:1
Grade: 10

Australian Standard: AS 3776


Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Grab Hook OG

Blueprint



Technical data

Part Code	Code	WLL ton	B mm	E mm	F mm	L mm	Weight (kg)
402300260290	OG-7/8-10	2.6	10	17	10	65	0.3
402300400290	OG-10-10	4	12	20	12	85	0.7
402300680290	OG-13-10	6.8	16	26	16	104	1.6
402301030290	OG-16-10	10.3	20	32	19	131	2.8
402301600290	OG-20-10	16	26	41	23	167	6.1
402302000290	OG-22-10	20	26	46	26	187	7.75
402302730290	OG-26-10	27.3	32	55	38	228	14
402304000290	OG-32-10	40	40	50	27	229	20.7

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved