



## Grab Hook OG

### Product information

Eye shortening hook. No reduction of working load limit, thanks to supporting lugs on either side of hook to prevent chain link deformation.

**Material:** Quenched and tempered alloy steel.

**Marking:** According to standard, code and grade.

**Finish:** Painted.

**Standard:** EN 1677

**Warning:** Not to be heat treated.

**Safety factor:** 4:1

**Grade:** 10

**Australian Standard:** AS 3776

| Part Code    | Code      | WLL ton | B mm | E mm | F mm | L mm | Weight (kg) |
|--------------|-----------|---------|------|------|------|------|-------------|
| 402300260290 | OG-7/8-10 | 2.6     | 10   | 17   | 10   | 65   | 0.3         |
| 402300400290 | OG-10-10  | 4       | 12   | 20   | 12   | 85   | 0.7         |
| 402300680290 | OG-13-10  | 6.8     | 16   | 26   | 16   | 104  | 1.6         |
| 402301030290 | OG-16-10  | 10.3    | 20   | 32   | 19   | 131  | 2.8         |
| 402301600290 | OG-20-10  | 16      | 26   | 41   | 23   | 167  | 6.1         |
| 402302000290 | OG-22-10  | 20      | 26   | 46   | 26   | 187  | 7.75        |
| 402302730290 | OG-26-10  | 27.3    | 32   | 55   | 38   | 228  | 14          |
| 402304000290 | OG-32-10  | 40      | 40   | 50   | 27   | 229  | 20.7        |

## Blueprint

