

## Coupling Link Gunnebo, G Grabiq

---

### Product information



For use with master link and eye hook.

... [Read more](#)

**Material:** Quenched and tempered alloy steel.

**Marking:** According to standard, code and grade.

**Finish:** Painted.

**Standard:** EN 1677

**Warning:** Not to be heat treated.


**Safety factor:** 4:1

**Grade:** 10

**Australian Standard:** AS 3776

## Coupling Link Gunnebo, G Grabiq

### Blueprint



### Technical data

| Part Code    | Code    | Chain size mm | WLL ton | A mm | B mm | C mm | F mm | L mm | Weight (kg) |
|--------------|---------|---------------|---------|------|------|------|------|------|-------------|
| 402200150090 | G-6-10  | 6             | 1.5     | 8    | 15   | 16   | 7    | 45   | 0.1         |
| 402200200090 | G-7-10  | 7             | 2       | 11   | 18   | 22   | 9    | 56   | 0.2         |
| 402200260090 | G-8-10  | 8             | 2.6     | 11   | 18   | 22   | 9    | 56   | 0.2         |
| 402200400090 | G-10-10 | 10            | 4       | 13   | 25   | 26   | 12   | 68   | 0.3         |
| 402200680090 | G-13-10 | 13            | 6.8     | 17   | 29   | 33   | 15   | 89   | 0.7         |
| 402201030090 | G-16-10 | 16            | 10.3    | 20   | 36   | 40   | 19   | 106  | 1.4         |
| 402201600090 | G-20-10 | 20            | 16      | 26   | 43   | 44   | 23   | 125  | 2.2         |
| 402202000090 | G-22-10 | 22            | 20      | 28   | 50   | 59   | 26   | 152  | 3.6         |
| 402202730090 | G-26-10 | 26            | 27.3    | 34   | 58   | 61   | 32   | 161  | 5.7         |
| 402204000090 | G-32-10 | 32            | 40      | 40   | 70   | 77   | 38   | 200  | 9.5         |