

## Lever Block GLG Overload

## **Product information**

The Global Overload Lever Block uses the latest technology to ensure a higher quality design, operator safety and longer service life.

- Suitable for applications in the mining, construction, transport and automotive industry.
- "T"-type latch for improved load holding integrity (except for the 250kg capacity)
- New design double pawl safety spring to eliminate sticking
- New style cast hand wheel for added strength and durability
- Encapsulated bearings and side plate bearings for smoother operation
- Key internal components are machined before being heat-treated and toughened
- No aluminum content which ensures suitability for mining applications
- Overall better design and improved finish to prolong life expectancy

| Part Code       | WLL<br>ton | Lifting height<br>m | A<br>mm | B<br>mm | C<br>mm | E<br>mm | H<br>mm | Weight<br>(kg) |
|-----------------|------------|---------------------|---------|---------|---------|---------|---------|----------------|
| 500500080150590 | 0.8        | 1.5                 | 148     | 135     | 295     | 26      | 290     | 7              |
| 500500160150590 | 1.6        | 1.5                 | 174     | 160     | 423     | 30      | 385     | 11             |
| 500500320150590 | 3.2        | 1.5                 | 193     | 209     | 423     | 34      | 477     | 20             |
| 500500630150590 | 6.3        | 1.5                 | 193     | 263     | 423     | 47      | 550     | 30             |
| 500500900150590 | 9          | 1.5                 | 193     | 366     | 423     | 64      | 720     | 46             |

## Blueprint

