

Lever Block Pacific OLL

Product information



The extensive range of Pacific Lever Blocks feature superior quality at an affordable price. They are suitable for applications in the mining, construction, transport and automotive industry. A patented Overload Limiting device is available to improve safety.


Features:

- “T” type hooks for improved load holding integrity (except for the 250kg capacity).
- New design double pawl safety springs to eliminate sticking
- New style cast hand wheel for added strength and durability
- Encapsulated needle bearings and side plate bearings for smoother operation.
- Brake lockout bearing for security of braking mechanism.
- Key internal components are CNC machined before being heat-treated and toughened.
- Fitted with high quality European zinc plated Grade 80 load chain.
- No aluminum content which ensures suitability for mining applications.
- Overall better design and improved finish to prolong life expectancy.

... [Read more](#)

Lever Block Pacific OLL

Blueprint



Technical data

| Part Code | WLL ton | Lifting height m | Number of falls | Amm mm | B mm | Cmm mm | Dmm mm | Emm mm | Fmm mm | Gmm mm | Weight (kg) |
|-----------------|---------|------------------|-----------------|--------|------|--------|--------|--------|--------|--------|-------------|
| 500500050150800 | 0.5 | 1.5 | 1 | 143 | 85 | 118 | 310 | 253 | 22 | Ø20 | 4.42 |
| 500500080150800 | 0.8 | 1.5 | 1 | 147 | 87 | 132 | 340 | 273 | 26 | Ø25 | 5.71 |
| 500500160150800 | 1.6 | 1.5 | 1 | 173 | 99 | 145 | 400 | 378 | 29 | Ø30 | 9.27 |
| 500500320150800 | 3.2 | 1.5 | 1 | 200 | 112 | 198 | 520 | 418 | 37 | Ø36 | 16.5 |
| 500500630150800 | 6.3 | 1.5 | 2 | 200 | 112 | 230 | 640 | 418 | 43 | Ø43 | 21.29 |