



## Lever Hoist NR Vital

### Product information

The NR-Series lever blocks feature the “free-wheeling” braking system which enables fast and easy operation. There is a minimum load requirement of 10% of the Working Load Limit to ensure that the braking system remains operative and continues to support the load. These lever blocks are ideally suited for the shipbuilding, construction, mining and power transmission industries.

This leverhoist comes in 1 or 1.5 m lift height as standard. Other sizes can be provided up on request.

**Material:** Steel

**Marking:** According to standard, CE-marked, WLL, serial number

**Temperature range:** -10°C til +50°C

**Standard:** EN 13157, EN 818-7

**Safety factor:** 4:1

<b>Part Code</b>	<b>WLL ton</b>	<b>Lifting height m</b>	<b>Headroom mm</b>	<b>Weight (kg)</b>
500500030100430	0.25	1	230	1.9
500500030150430	0.25	1.5	230	1.9
500500050150430	0.5	1.5	260	3.5
500500050300430	0.5	3	260	6
500500080150430	0.8	1.5	295	6
500500100150430	1	1.5	325	7.2
500500160150430	1.6	1.5	350	9.8
500500320150430	3.2	1.5	425	16.6
500500320200430	3.2	2	425	17
500500630150430	6.3	1.5	565	27
500500900150430	9	1.5	680	47.3