Lifting Solutions Group
Axel Johnson International

Clevis Masterlink X-059

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
... Read more

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.
Temperature range: -40° up to +200°C (without reduction in WLL).
Finish: Blue painted.
Standard: EN 1677-4
AS 3776

Safety factor: 4:1
Grade: 10


Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Clevis Masterlink X-059

Blueprint



Technical data

Part Code	Chain size mm	WLL ton	EWL mm	A mm	G mm	H mm	K mm	L mm	T mm	Weight (kg)
402100250510	7-8	2.5	99	10	65	15	103	83	19	0.4
402100400510	10	4	125	11	96	19	133	108	19	0.8
402100670510	13	6.7	168	14	108	22	168	136	25	1.5
402101000510	16	10	198	18	124	26	203	165	27	2.4

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved