Lifting Solutions Group
Axel Johnson International

Swivel Lifting Point

Product information

Large ring bolt used as a swiveling load ring able to swivel 360° with a pivot of 180°.

... *Read more*



Material: Alloy steel
Marking: According to standard, WLL, size, manufacturer
Finish: Orange painted
Standard: EN 818-4
Note: Not suitable for turning under full load at 90° in the side loading position
Warning: These eyebolts are not designed for permanently rotating continuously


Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Swivel Lifting Point

Blueprint



Technical data

Part Code	WLL ton	Thread	Ø mm mm	A mm	C mm	D mm	E mm	M mm	L mm	L1 mm	Weight (kg)
4215605208	0.3	M8	14	30	35	55	52.5	8	10.4	35.6	0.36
4215605210	0.63	M10	14	30	35	55	52.5	10	16	36	0.38
4215605212	1	M12	18	36	40	68	54	12	18	44	0.71
4215605214	1.22	M14	18	36	40	68	54	14	21	45	0.72
4215605216	1.5	M16	18	36	40	68	54	16	24	46	0.74
4215605218	2	M18	16	50	54	83	80	18	26	57	1.16
4215605220	2.5	M20	16	50	54	83	80	20	30	58	1.21
4215605224	4	M24	18	50	54	83	94	24	60	35	1.37
4215605227	4	M27	27	68	73	119	106	27	38	82	4.18
4215605230	5	M30	27	68	73	119	106	30	48	84	4.4
4215605236	8	M36	31	86	94	148	140.5	36	62	101	7.6
4215605242	15	-	-	-	-	-	-	-	43	-	-

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved