

Forged Open Spelter Wire Rope Socket

Product information




- YOKE Spelter Sockets are forged from special bar quality carbon steel with very finest hardness controlled.
- YOKE Spelter Sockets properly applied have an efficiency rating of 100% based on the catalog strength of wire rope.
- Socket size 1/4" thru 3/4" use one groove, 7/8" thru 1-1/2" use 2 grooves.
- Open Spelter sockets meet the performance requirements of Federal Specification RR-S550E, Type A.
- Galvanized or Self Colored finish

[... Read more](#)

Forged Open Spelter Wire Rope Socket

Blueprint



Technical data

Part Code	Rope diameter mm	Finish	A mm	C mm	D mm	D1 mm	d mm	H mm	K mm	L mm	T mm	W mm	Weight (kg)
122100700452	6-7	Galvanized	33	9	18	17	11	57	40	115	39	23	0.5
122100700455	6-7	Painted	33	9	18	17	11	57	40	115	39	23	0.5
122101000452	8-10	Galvanized	38	11	21	20	13	57	45	123	44	21	0.6
122101000455	8-10	Painted	38	11	21	20	13	57	45	123	44	21	0.6
122101300452	11-13	Galvanized	48	13	25	25	15	63	54	142	50	25	1.1
122101300455	11-13	Painted	48	13	25	25	15	63	54	142	50	25	1.1
122101600452	14-16	Galvanized	58	14	29	30	18	76	64	172	57	32	1.8
122101600455	14-16	Painted	58	14	29	30	18	76	64	172	57	32	1.8
122102000452	18-20	Galvanized	67	16	32	35	22	92	76	202	67	38	2.6
122102000455	18-20	Painted	67	16	32	35	22	92	76	202	67	38	2.6
122102300452	22-23	Galvanized	80	20	38	41	24	102	89	235	85	45	4.7
122102300455	22-23	Painted	80	20	38	41	24	102	89	235	85	45	4.7
122102600452	24-26	Galvanized	96	23	44	51	29	114	102	268	95	52	7.4
122102600455	24-26	Painted	96	23	44	51	29	114	102	268	95	52	7.4
122103000452	28-30	Galvanized	105	25	51	56	32	127	117	300	105	57	10.1
122103000455	28-30	Painted	105	25	51	56	32	127	117	300	105	57	10.1
122103500452	32-35	Galvanized	121	29	57	62	38	140	127	335	120	64	14.9
122103500455	32-35	Painted	121	29	57	62	38	140	127	335	120	64	14.9
122103900452	36-39	Galvanized	137	30	70	70	41	152	152	384	133	76	20.7
122103900455	36-39	Painted	137	30	70	70	41	152	152	384	133	76	20.7