Lifting Solutions Group
Axel Johnson International

Ferrule R End stop Talurit®

Product information



Round ferrule (R) is intended to be pressed on single layer round strand wire ropes, for instance on preventer wires or used as end stop.

The expected strength regarding this end-termination is approximately 50% of the MBL of the wire rope (informative only).

Round aluminium end stops are not recommended for use in high strength applications.

... *Read more*

Material: Aluminum
Note: See the manufacturer's product data sheet below for guidance on dimension selection.
Warning: Ends stops (R) are not allowed to use for lifting applications.

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Ferrule R End stop Talurit®

Technical data

Part Code	Ferrule size mm
1205R03	3
1205R04	4
1205R05	5
1205R06	6
1205R065	6.5
1205R07	7
1205R08	8
1205R09	9
1205R10	10
1205R11	11
1205R12	12
1205R13	13
1205R14	14
1205R015	1.5
1205R16	16
1205R02	2
1205R18	18
1205R20	20
1205R22	22
1205R24	24
1205R26	26
1205R28	28
1205R30	30
1205R32	32

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved