
Lifting Solutions Group
Axel Johnson International

Chain KLB, Gunnebo Short Link lifting chain

Product information



Quality blue painted Chain KLB Short Link KL, Grade 80, quenched and tempered
... Read more

Marking: According to standard
Finish: Quenched and tempered.
Standard: EN 818-2

Safety factor: 4:1
Grade: 8


Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Chain KLB, Gunnebo Short Link lifting chain

Blueprint



Technical data

Part Code	Chain size mm	WLL ton	Min. breaking force kN	Length m	d mm	P mm	w1mm mm	Weight kg/m
203100602000120	6	1.1	45.2	200	6	18	8.5	0.8
203100702000120	7	1.5	62	200	7	21	10	1.1
203100802000120	8	2	80.6	200	8	24	11	1.4
203101001000120	10	3.2	130	100	10	30	14	2.3
203101301000120	13	5.4	214	100	13	39	17.7	3.8
203101601000120	16	8.2	322	100	16	48	21.9	5.6
203101901000120	19	11.6	457	100	19	57	27	7.8
203102200500120	22	15.5	610	50	22	66	29.5	10.6
203102600500120	26	21.6	850	50	26	78	35	14.8
203103200500120	32	32.8	1,300	25	32	96	44.6	21.6

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved