

## Load Brake Winch OzWinch SF2200

---

### Product information



The OzWinch SF2200 Load Brake Winch has been specifically designed for safer and easier winch operation in both hoisting and hauling applications. Requiring very low effort to easily operate, the reciprocating ratchet handle allows simple handle movement in either direction for both lifting and lowering loads which is ideal for use in cramped locations.

The SF2200 is also equipped with a positive load-actuated brake and can hold the load safely in any position while the gears and brake are fully covered to prevent dust, dirt and rain contamination.

[... Read more](#)

---


**Marking:** According to standard

**Standard:** AS 1418

**Note:** Steel wire ropes must be ordered separately

## Load Brake Winch OzWinch SF2200

Blueprint



Technical data

| Part Code       | WLL<br>ton | Rope<br>Ø<br>mm | Rope<br>capacity<br>m | Pulling<br>capacity<br>t | Amm<br>mm | B<br>mm | Cmm<br>mm | Dmm<br>mm | Emm<br>mm | Fmm<br>mm | Gmm<br>mm | Hmm<br>mm | Imm<br>mm | Jmm<br>mm | Kmm<br>mm | Lmm<br>mm | Mmm<br>mm | Nmm<br>mm | Omm<br>mm | Pmm<br>mm | Qmm<br>mm | Rmm<br>mm | S<br>mm | Tmm<br>mm | V<br>mm | Weight<br>(kg) |
|-----------------|------------|-----------------|-----------------------|--------------------------|-----------|---------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|---------|-----------|---------|----------------|
| 501300100000810 | 1          | 8               | 32                    | 2                        | 100       | 54      | 238       | 214       | 108       | 300       | 156       | 16Ø       | 155Ø      | 80Ø       | 118       | 224       | 342       | 238       | 198       | 130       | 224       | 150       | 13      | 50        | 13Ø     | 17.5           |