Lifting Solutions Group
Axel Johnson International

Manila 3-Strand

Product information



The strongest of all-natural fiber ropes. Manila rope is used in many general commercial/industrial applications as well as decorative applications.

Elongation at break: Approx. 16%.

Specific gravity: Approx. 1.48 g/cm^3.

Water absorption: 30%.

Quality: Grade II

... *Read more*

Rope construction: 3-strand.
Material: Manila natural fibre.
Finish: Brown (natural-coloured).

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Manila 3-Strand

Technical data

Part Code	Diameter mm	MBL ton ton	Weight kg/220m
300300600000160	6	0.26	7
300300800000160	8	0.419	12
300301000000160	10	0.559	15
300301200000160	12	0.95	25
300301400000160	14	1.2	31
300301600000160	16	1.71	42
300301800000160	18	2.1	51
300302000000160	20	2.805	62
300302200000160	22	3.325	77
300302400000160	24	3.925	95
300302600000160	26	5.3	103
300302800000160	28	5.225	128
300303200000160	32	6.665	165
300303600000160	36	7.572	196

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved