Lifting Solutions Group
Axel Johnson International

Polyester Fibre Rope, 3-Strand

Product information



Polyester rope to be used as mooring- or anchor-rope on pleasure boats.

Design: Polyester wool reinforced with polyester silk results in an especially soft and knot secure rope.
Specific gravity: 1,38 (sinks).
Melting point: apx 260°C.
Elongation: apx 35%

... *Read more*

Material: Polyester has very good resistance against UV-radiation, acids, mild alkalies and rot.
Finish: White.

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Polyester Fibre Rope, 3-Strand

Technical data

Part Code	Diameter mm	Min. breaking force kN	Length m	Rope ends	Weight kg/220m
300300802200020	8	8.3	220	Plain ends	8.6
300301002200020	10	10.8	220	Plain ends	13
300301000000020	10	10.8	-	Plain ends	-
300301202200020	12	16.7	220	Plain ends	20
300301200000020	12	16.7	-	Plain ends	-
300301402200020	14	21.1	220	Plain ends	26
300301400000020	14	21.1	-	Plain ends	-
300301602200020	16	27.9	220	Plain ends	35
300301602500020	16	39.81	250	Plain ends	-
300301802200020	18	32.8	220	Plain ends	43

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved