

Master Link Assembly MT GrabiQ V2

Product information



Designed for use with chain, wire or synthetic rope. For 3-leg and 4-leg slings
... [Read more](#)

Material: Alloy Steel

Marking: According to standard, Code, grade, chain size, manufacturing ID

Finish: Painted


Standard: EN 1677-4 (+25% WLL) , AS 3775, AS 3776

Safety factor: 5:1

Grade: 10

Master Link Assembly MT GrabiQ V2

Blueprint



Technical data

Part Code	Code	WLL ton	L1 mm	L mm	E mm	D mm	l mm	e mm	d mm	Weight (kg)
402100431200	MT-6-10 GrabiQ V2	4.3	260	140	80	17	120	60	13	1.5
402100781200	MT-8-10 GrabiQ V2	7.8	300	160	95	22	140	80	17	3
402101201200	MT-10-10 GrabiQ V2	12	435	275	145	28	160	95	22	6.8
402102101200	MT-13-10 GrabiQ V2	21	465	275	145	32	190	110	28	10.9
402103101200	MT-16-10 GrabiQ V2	31	545	270	140	40	275	145	32	18.4
402104801200	MT-20-10 GrabiQ V2	48	610	340	180	45	270	140	40	29.1
402106001200	MT-22-10 GrabiQ V2	60	690	350	200	55	340	180	45	46.4
402108501200	MT-26-10 GrabiQ V2	85	725	375	210	60	350	200	55	67.6
402112501200	MT-32-10 GrabiQ V2	125	825	450	260	80	375	210	60	110.1