



## Round Sling - Blackline

### Product information

#### **POWERTEX**

Typically used in connection with theaters, scenes etc. where the round sling preferably should not be visible.

Design: Load carrying yarn covered with "seamless" black protection sleeve.

Stretch with working load: 2-3%.

Length tolerance: Nominal length (EWL)  $\pm 2\%$ .

**Material:** Polyester. Resistant to most acids but not to strong alkalizes.

**Marking:** According to standard, CE-marked, Manufacture ID, WLL, length, date.

**Temperature range:** Approx.  $-40^{\circ}$  up to  $+100^{\circ}\text{C}$ .

**Standard:** EN 1492-2

AS 4497

**Safety factor:** 7:1

Part Code	Code	WLL ton	EWL m	WLL Straight Lift ton	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	WLL 0-45° t	Colour
340100100250160	-	1	2.5	-	-	-	-	-	-	Black
340100100400160	-	1	4	-	-	-	-	-	-	Black
340100110100160	PRS-011.B	1.1	1	1.1	0.9	2.2	1.5	1.1	1.5	Black
340100110200160	PRS-011.B	1.1	2	1.1	0.9	2.2	1.5	1.1	1.5	Black
340100110300160	PRS-011.B	1.1	3	1.1	0.9	2.2	1.5	1.1	1.5	Black
340100210100160	PRS-021.B	2.1	1	2.1	1.7	4.2	2.9	2.1	2.9	Black
340100210200160	PRS-021.B	2.1	2	2.1	1.7	4.2	2.9	2.1	2.9	Black
340100210300160	PRS-021.B	2.1	3	2.1	1.7	4.2	2.9	2.1	2.9	Black
340100310100160	PRS-031.B	3.1	1	3.1	2.5	6.2	4.3	3.1	4.3	Black
340100310200160	PRS-031.B	3.1	2	3.1	2.5	6.2	4.3	3.1	4.3	Black
340100310300160	PRS-031.B	3.1	3	3.1	2.5	6.2	4.3	3.1	4.3	Black

## Blueprint

