Lifting Solutions Group
Axel Johnson International

Spur Gear Hand Winch TL1000-1500 Painted

Product information

This spur gear winch is fast, easy and can be mounted on both walls and floors. The free spool option is therefore also available for this winch. In addition to IP54 water resistance, this winch is also available in stainless steel 304.

- Robust and safe lifting and pulling winch
- Protection classification IP54
- Load pressure brake with double ratchet system for safe stable hold of the load in any position
- Cable outlet upwards, downwards or at the left
- Closed gearbox to protect against environmental influence
- Adjustable crank
- Suitable for wall and floor mounting
- 1 layer of paint

Options:

- Zinc-plated finish 6 - 8 micron (EV)
- 2 layers of paint (2L)
- Stainless steel grade 304 (SST304)
- 2 drum compartment (2D)
- Free-spooling device for pulling applications. To disengage the drum (FS)
- ATEX certified zone 2 and 22 (EX)

  CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C
  CE II 3D Ex IIIC T135°C Dc, -20°C<T amb <+70°C

... *Read more*

Material: Steel
Marking: According to standard, CE-marked
Temperature range: -20°C up to +70°C
Finish: Painted, grey
Standard: EN 13157
Note: The cable must be ordered separately, ask for more information about our sales

Safety factor: 4:1

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Spur Gear Hand Winch TL1000-1500 Painted

Blueprint



Technical data

Part Code	Code	WLL ton	Rope Ø mm	Rope capacity m	Capacity 1st layer kg	Capacity top layer kg	Weight (kg)
501300100000570	TL1000	1	8	33	1,000	614	27
501300150000570	TL1500	1.5	10	21	1,500	927	27.5

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved