

Spur Gear Hand Winch TL300-600 Painted

Product information



This convenient spur gear winch excels by its speed. It is equipped with a load-pressure brake with a double ratchet system and a semi-closed housing.

- Robust and safe lifting and pulling winch
- Load pressure brake with double ratchet system for safe stable hold of the load in any position
- Cable outlet upwards
- Adjustable crank
- Suitable for wall mounting
- 1 layer of paint

Options:

- Zinc-plated finish 6 - 8 micron (EV)
- 2 layers of paint (2L)
- ATEX certified zone 2 and 22 (EX)
CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C
CE II 3D Ex IIIC T135°C Dc, -20°C<T amb <+70°C

... [Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +70°C

Finish: Painted, grey


Standard: EN 13157

Note: The cable must be ordered separately, ask for more information about our sales

Safety factor: 4:1

Spur Gear Hand Winch TL300-600 Painted

Blueprint



Technical data

Part Code	Code	WLL ton	Rope Ø mm	Rope capacity m	Capacity 1st layer kg	Capacity top layer kg	Weight (kg)
501300030000560	TL300	0.3	4	35.4	300	172	10
501300060000560	TL600	0.6	6	12.3	600	336	11