


## Wire Rope Dyform 8 PI

### Product information



Dyform 8 PI is a high performance compacted single layer constructed rope which incorporates a plastic layer between the 8 outer strands.

- Improved bending fatigue performance
- Stable rope construction
- Diameter stability, requirement of multi-layered spooling

**Temperature range:** -53°C up to +100°C

**Fill factor:** 0,68

**Tolerance Ø:** 0% to +5%

Part Code	Rope diameter	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay	Min. breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Weight
103101104270859	11	1,960	Galvanized	sZ	110	-	SupplierStandard	57
103101204270859	12	1,960	Galvanized	sZ	128	-	SupplierStandard	67
103101304990859	13	1,960	Galvanized	sZ	150	-	SupplierStandard	79
103102004990859	20	1,960	Galvanized	sZ	353	-	SupplierStandard	188
103102204270859	22	1,960	Galvanized	sZ	427	-	SupplierStandard	228
103102203270859	22	1,960	Galvanized	zS	427	-	SupplierStandard	228
103102406270859	24	1,960	Galvanized	zZ	508	-	SupplierStandard	271

103102405270859	24	1,960	Galvanized	sS	508	-	SupplierStandard	271
103102406300859	24	2,160	Galvanized	zZ	531	-	SupplierStandard	271
103102605270859	26	1,960	Galvanized	sS	596	-	SupplierStandard	318
103102606270859	26	1,960	Galvanized	zZ	596	-	SupplierStandard	318
103102604270859	26	1,960	Galvanized	sZ	596	-	SupplierStandard	318
103102603270859	26	1,960	Galvanized	zS	596	-	SupplierStandard	318
103102603300859	26	2,160	Galvanized	zS	623	-	SupplierStandard	318
103102805270859	28	1,960	Galvanized	sS	691	-	SupplierStandard	369
103102806270859	28	1,960	Galvanized	zZ	691	-	SupplierStandard	369
103102804300859	28	2,160	Galvanized	sZ	723	-	SupplierStandard	369
103103005270859	30	1,960	Galvanized	sS	794	-	SupplierStandard	424
103103006270859	30	1,960	Galvanized	zZ	794	-	SupplierStandard	424
103103205270859	32	1,960	Galvanized	sS	903	-	SupplierStandard	482
103103206270859	32	1,960	Galvanized	zZ	903	-	SupplierStandard	482
103103405270859	34	1,960	Galvanized	sS	1,020	-	SupplierStandard	544
103103404270859	34	1,960	Galvanized	sZ	1,020	-	SupplierStandard	544
103103403270859	34	1,960	Galvanized	zS	1,020	-	SupplierStandard	544
103104003270859	40	1,960	Galvanized	zS	1,410	-	SupplierStandard	74
103104004270859	40	1,960	Galvanized	sZ	1,410	-	SupplierStandard	754
103104206270859	42	1,960	Galvanized	zZ	1,560	-	SupplierStandard	831
103104206270856	42	1,960	Galvanized	zZ	1,560	-	C mm	831
103105004300859	50	2,160	Galvanized	sZ	2,089.9	-	SupplierStandard	1,110