Lifting Solutions Group
Axel Johnson International

Ferrule INOX Talurit®

Product information



These ferrules are normally used on stainless steel wire ropes to achieve the best possible resistance against corrosion.

Stainless steel Ferrule - recommended for machine pressing only. Suitable for long term use in salt water, waste water treatment and chemical processing ... *Read more*

Material: Stainless steel, AISI 316.
Note: See the manufacturer's product data sheet below for guidance on dimension selection. We do not guarantee strength of slings for lifting activities made of INOX ferrules. A termination performed according to our instructions will normally withstand a tensile strength of 90% of the minimum-breaking load (MBL) of the wire rope. Verifying tests must be done in order to find out the strength.

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Ferrule INOX Talurit®

Technical data

Part Code	Ferrule size mm
120100100110	1
120100150110	1.5
120100200110	2
120100250110	2.5
120100300110	3
120100350110	3.5
120100400110	4
120100450110	4.5
120100500110	5
120100600110	6
120100700110	7
120100800110	8
120100900110	9
120101000110	10
120101100110	11
120101200110	12
120101300110	13
120101400110	14
120101600110	16
120101800110	18
120102000110	20
120102200110	22
120102400110	24
120102700110	26
120102800110	28
120103000110	30
120103200110	32

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved