Lifting Solutions Group
Axel Johnson International

Open Spelter Socket BN Green Pin® G-6422

Product information



The Green Pin® Open Spelter Socket BN is an open spelter socket with a safety bolt. The socket offers a double safety (split pin and safety bolt) which prevents accidental unscrewing of the pin. The socket is made from high tensile steel, while galvanization ensures its long-term durability. The Green Pin® Open Spelter Socket BN is available for wire rope with a diameter from 6-7 up to 40-42 mm and can be used in combination with the Socket Lock Socketing Resin.

Certification on request: 2.1, 2.2, 3.1

... *Read more*

Material: high tensile steel
Marking: CE-marked
Temperature range: -20°C up to +200°C
Finish: hot dipped galvanized

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Open Spelter Socket BN Green Pin® G-6422

Blueprint



Technical data

Part Code	Rope diameter mm	MBL ton ton	a mm	b mm	c mm	d mm	e mm	f mm	Weight (kg)
121500700340	6-7	8	109	69	19	16	33	9	0.53
121501000340	8-10	12	124	83	21	20	35	12	0.86
121501300340	11-13	20	143	101	26	25	37	15	1.4
121501600340	14-16	25	172	124	33	30	49	18	2.32
121501900340	18-19	45	205	138	38	35	58	21	3.81
121502200340	20-22	50	235	148	44	41	68	24	5.56
121502600340	23-26	85	275	176	51	50	76	28	9.9
121503000340	27-30	105	306	193	57	57	85	32	13.8
121503600340	31-36	136	338	210	63	63	95	38	18.9
121503900340	37-39	150	394	230	76	70	127	41	27.1
121504200340	40-42	170	418	244	76	77	126	44	32.7

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved