Lifting Solutions Group
Axel Johnson International

Forged Closed Spelter Wire Rope Socket

Product information



- YOKE Spelter are forged from special bar quality carbon steel with very finest hardness controlled.
- YOKE Spelter properly applied have an efficiency rating of 100% based on the catalog strength of wire rope.
- Socket size 1/4" thru 3/4" use one groove, 7/8" thru 1-1/2" use 2 grooves.
- Closed Spelter sockets meet the performance requirements of Federal Specification RR-S-550E,Type B.

... *Read more*

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Forged Closed Spelter Wire Rope Socket

Blueprint



Technical data

Part Code	Rope diameter mm	Finish	A mm	B mm	D mm	D1 mm	d mm	H mm	K mm	L mm	T mm	W mm	Weight (kg)
122100700465	6-7	Painted	38	13	18	22	11	57	44	114	38	13	0.3
122101000465	8-10	Painted	43	16	21	25	13	57	51	124	43	18	0.4
122101300465	11-13	Painted	51	18	25	30	14	64	57	138	50	22	0.7
122101600465	14-16	Painted	67	21	28	36	18	76	64	160	63	25	1.2
122102000465	18-20	Painted	76	27	32	41	21	89	76	192	70	32	2
122102300465	22-23	Painted	92	32	38	48	24	101	89	222	88	38	3.6
122102600465	24-26	Painted	104	35	45	58	29	114	102	251	96	45	4.9
122103000465	28-30	Painted	114	38	51	65	32	127	114	279	105	50	7.2
122103500465	32-35	Painted	135	41	57	71	38	140	127	308	121	57	10.5
122103900465	36-39	Painted	135	49	70	81	41	152	152	354	133	64	14.3

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved