

Webbing Slings B4

Product information

Four-layer lifting slings. The width of the sling is increased in relation to the lifting capacity. Ideal for areas where minimum surface pressure is required on the load to be lifted, such as boat lifting. Reinforced folding eyelets as standard.

[... Read more](#)



Material: 100% polyester

Marking: According to standard, CE-marked

Temperature range: -40°C up to +100°C

Standard: EN 1492-1

Note: Color coded

Webbing Slings B4

Technical data

WLL ton	EWL m	Webbing width mm	Colour
2	1	30	Green
2	2	30	Green
2	3	30	Green
2	4	30	Green
2	5	30	Green
2	6	30	Green
2	7	30	Green
2	8	30	Green
2	9	30	Green
2	10	30	Green
4	1	60	Grey
4	2	60	Grey
4	3	60	Grey
4	4	60	Grey
4	5	60	Grey
4	6	60	Grey
4	7	60	Grey
4	8	60	Grey
4	9	60	Grey
4	10	60	Grey
6	2	90	Brown
6	3	90	Brown
6	4	90	Brown
6	5	90	Brown
6	6	90	Brown
6	7	90	Brown
6	8	90	Brown
6	9	90	Brown
6	10	90	Brown
8	2	120	Blue
8	3	120	Blue

Webbing Slings B4

Technical data

WLL ton	EWL m	Webbing width mm	Colour
8	4	120	Blue
8	5	120	Blue
8	6	120	Blue
8	7	120	Blue
8	8	120	Blue
8	9	120	Blue
8	10	120	Blue
10	3	150	Orange
10	4	150	Orange
10	5	150	Orange
10	6	150	Orange
10	7	150	Orange
10	8	150	Orange
10	9	150	Orange
10	10	150	Orange
16	3	240	Orange
16	4	240	Orange
16	5	240	Orange
16	6	240	Orange
16	7	240	Orange
16	8	240	Orange
16	9	240	Orange
16	10	240	Orange
20	3	300	Orange
20	4	300	Orange
20	5	300	Orange
20	6	300	Orange
20	7	300	Orange
20	8	300	Orange
20	9	300	Orange
20	10	300	Orange

Webbing Slings B4

Technical data

WLL ton	EWL m	Webbing width mm	Colour
24	3	300	Orange
24	4	300	Orange
24	5	300	Orange
24	6	300	Orange
24	7	300	Orange
24	8	300	Orange
24	9	300	Orange
24	10	300	Orange