Lifting Solutions Group
Axel Johnson International

Half Coupling Link 8-054

Product information



- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- To combine with 8-088N Insulated Blank Swivel

... *Read more*

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard
Temperature range: Tempering temperature minimum 400°C
Standard: EN 1677-1

Safety factor: 4:1
Grade: 8


Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Half Coupling Link 8-054

Blueprint



Technical data

Part Code	Chain size mm	WLL ton	A mm	D mm	K mm	L mm	Weight (kg)
401200110140	6	1.12	15	7	17	22	0.1
401200200140	7-8	2	18	9	22	28	0.1
401200320140	10	3.15	25	11	26	34	0.2
401200530140	13	5.3	30	16	35	45	0.4
401200800140	16	8	36	19	38	50	0.6
401201250140	18-20	12.5	42	22	46	60	1.1
401201500140	22	15	49	24	59	76	1.7
401202120140	26	21.2	55	30	62	80	2.7
401203150140	32	31.5	69	36	79	100	5

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved