Lifting Solutions Group
Axel Johnson International

Eye Grab Hook 8-041, Yoke

Product information



- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

... *Read more*

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard
Temperature range: -40°C up to +200°C
Finish: Powder coating
Standard: EN 1677-1

Safety factor: 4:1
Grade: 8

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Eye Grab Hook 8-041, Yoke

Blueprint



Technical data

Part Code	Chain size mm	WLL ton	A mm	F mm	G mm	K mm	P mm	Weight (kg)
401300110930	6	1.12	13	30	8	51	8	0.2
401300200930	7-8	2	15	30	9	60	10	0.3
401300320930	10	3.15	20	41	13	84	13	0.6
401300530930	13	5.3	25	52	15	102	16	1.4
401300800930	16	8	30	57	20	114	20	2.3
401301250930	18-22	12.5	36	73	24	132	23	3.9
401301500930	22	15	38	70	26	165	26	4.7
401302120930	26	21.2	41	100	32	187	29	9.9
401303150930	32	31.5	61	127	40	230	37	21.4

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved