

Eye Grab Hook 8-041, Yoke

Product information



- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

... [Read more](#)

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard

Temperature range: -40°C up to +200°C

Finish: Powder coating


Standard: EN 1677-1

Safety factor: 4:1

Grade: 8

Eye Grab Hook 8-041, Yoke

Blueprint



Technical data

Part Code	Chain size mm	WLL ton	A mm	F mm	G mm	K mm	P mm	Weight (kg)
401300110930	6	1.12	13	30	8	51	8	0.2
401300200930	7-8	2	15	30	9	60	10	0.3
401300320930	10	3.15	20	41	13	84	13	0.6
401300530930	13	5.3	25	52	15	102	16	1.4
401300800930	16	8	30	57	20	114	20	2.3
401301250930	18-22	12.5	36	73	24	132	23	3.9
401301500930	22	15	38	70	26	165	26	4.7
401302120930	26	21.2	41	100	32	187	29	9.9
401303150930	32	31.5	61	127	40	230	37	21.4