

Swivel Self Locking Hook 8-027

Product information



- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

... [Read more](#)

Material: Alloy Steel - Quenched and Tempered

Marking: According to standard

Temperature range: Tempering temperature minimum 400°C


Standard: EN 1677-3

Safety factor: 4:1

Grade: 8

Swivel Self Locking Hook 8-027

Blueprint



Technical data

Part Code	Code	Chain size mm	WLL ton	A mm	B mm	D mm	H mm	K mm	P mm	T mm	Weight (kg)
420500110860	YE	6	1.12	31	22	12	19	149	29	15	0.7
420500200860	YE	8	2	36	29	14	24	186	34	20	1.2
420500320860	YE	10	3.15	40	34	16	30	220	44	26	2
420500530860	YE	13	5.3	46	43	22	39	267	52	30	4.1
420500800860	YE	16	8	60	50	24	49	328	60	36	7.2
420501250860	YE	20	12.5	75	82	26	62	388	90	48	11.5
420501500860	YE	22	15	97	95	33	63	457	80	49	18.6
420502120860	YE	26	21.2	123	115	52	69	535	99	56	31.9