Lifting Solutions Group
Axel Johnson International

RUD VRBS-FIX Lifting Ring

Product information



Load ring for plane surfaces. 180° pivoting. Continuous weld seam reduces likelihood of subsurface corrosion.

- No complex leveling of the components to each other
- No crevice corrosion: endless HY weld seam
- Clamping spring holds all parts together

... *Read more*

Material: CrNiMo Steel
Marking: According to standard, CE-marked
Temperature range: -20°C up to 200°C
Finish: Pink powder coated
Standard: EN 1677-1

Safety factor: 4:1

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

RUD VRBS-FIX Lifting Ring

Blueprint



Technical data

Part Code	Code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	T mm	Weight (kg)
42157999019	VRBS-FIX - 4t	4	60	14	39	48	132	69	74	0.94
42157999020	VRBS-FIX - 6.7t	6.7	88	20	50	60	167	91	97	2.24
42157999021	VRBS-FIX - 10t	10	100	22	60	65	191	100	108	3.72
42157999301	VRBS-FIX - 16t	16	130	30	72	90	267	134	140	8.23
42157999302	VRBS-FIX - 31.5t	31.5	160	42	99	130	366	195	202	18.36
42157906272	VRBS-FIX - 50t	50	246	70	148	230	596	335	330	64.7
42157906273	VRBS-FIX - 100t	100	320	97	195	250	763	392	390	148.2

© November 2026 - All Rights Reserved