

## RUD VRBS-FIX Lifting Ring

### Product information



Load ring for plane surfaces. 180° pivoting. Continuous weld seam reduces likelihood of subsurface corrosion.

- No complex leveling of the components to each other
- No crevice corrosion: endless HY weld seam
- Clamping spring holds all parts together

**Material:** CrNiMo Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to 200°C

**Finish:** Pink powder coated

**Standard:** EN 1677-1

**Safety factor:** 4:1

| Part Code   | Code             | WLL<br>ton | A<br>mm | B<br>mm | C<br>mm | D<br>mm | E<br>mm | F<br>mm | T<br>mm | Weight<br>(kg) |
|-------------|------------------|------------|---------|---------|---------|---------|---------|---------|---------|----------------|
| 42157999019 | VRBS-FIX - 4t    | 4          | 60      | 14      | 39      | 48      | 132     | 69      | 74      | 0.94           |
| 42157999020 | VRBS-FIX - 6.7t  | 6.7        | 88      | 20      | 50      | 60      | 167     | 91      | 97      | 2.24           |
| 42157999021 | VRBS-FIX - 10t   | 10         | 100     | 22      | 60      | 65      | 191     | 100     | 108     | 3.72           |
| 42157999301 | VRBS-FIX - 16t   | 16         | 130     | 30      | 72      | 90      | 267     | 134     | 140     | 8.23           |
| 42157999302 | VRBS-FIX - 31.5t | 31.5       | 160     | 42      | 99      | 130     | 366     | 195     | 202     | 18.36          |
| 42157906272 | VRBS-FIX - 50t   | 50         | 246     | 70      | 148     | 230     | 596     | 335     | 330     | 64.7           |
| 42157906273 | VRBS-FIX - 100t  | 100        | 320     | 97      | 195     | 250     | 763     | 392     | 390     | 148.2          |

## Technical data

---

## Blueprint

