Lifting Solutions Group
Axel Johnson International

Weld-on Point 8-0573

Product information

Classic weld-on point without spring.

- Pivots through 180°.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts are traceable to Test Certification.
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Lugs designed to assist the welding process.

... *Read more*

Material: Forged alloy steel, quenched and tempered.
Marking: According to standard, CE-marked, WLL
Standard: EN 1677-1
Note: Never apply load except in the same direction with the pivot direction.

Safety factor: 5:1 (WLL 1-8 ton), 4:1 (WLL 10-30 ton)

© September 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Weld-on Point 8-0573

Blueprint



Technical data

Part Code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	L mm	W mm	HV mm mm	a mm	Weight (kg)
42158057301	1	83	41	48	14	14	86	27	58	109	50	5	3	0.5
42158057303	3	98	48	58	17	17	85	31	54	114	58	6	3	0.9
42158057305	5	120	63	66	22	22	118	41	77	157	64	7	3	1.3
42158057308	8	121	73	68	26	26	122	53	69	169	60	10	4	2.4
42158057310	10	146	73	82	20	30	141	53	88	191	75	10	4	2.8
42158057320	20	186	93	100	25	37	175	70	105	234	91	20	4	6.5
42158057330	30	254	116	150	35	45	241	84	157	317	127	20	4	17.2

© September 2026 - All Rights Reserved