Lifting Solutions Group
Axel Johnson International

Lifting Point 8-204 UNC

Product information



- Rotates through 360° and pivot 180°, rated at 100% at 90°angle.
- Manufactured and tested in accordance with EN1677-1.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and cap screw are traceable to Test Certification.
- Bolt are UNC thread (ASME/ ANSI B18.31M).
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 1.5 times the WLL.
- Quick and simple assembly, just a tapped hole is required.

... *Read more*

Material: Alloy steel, quenched and tempered.
Marking: According to standard
Standard: EN 1677-1

Safety factor: 4:1

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lifting Point 8-204 UNC

Technical data

Part Code	WLL ton	Thread Inch
42158204004	0.36	5/16 -18
42158204005	0.45	3/8 -16
42158204010	1.3	1/2 -13
42158204019	1.81	5/8 -11
42158204021	2.27	3/4 -10
42158204042	3.63	7/8 -9
42158204045	4.54	1 -8
42158204070	6.8	1-1/4 -7
42158204125	10.89	1-1/2 -6
42158204135	13.61	2 -4.5

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved