

Turnbuckle Grade P Jaw Jaw

Product information

Generally used for straight or in line tensioning in conjunction with wire rope and or chain assemblies when heavy duty straining and lifting applications are required. Meets the design requirements of ASTM F1145:2017.

[... Read more](#)




Finish: Hot dipped galvanised

Safety factor: 5:1

Turnbuckle Grade P Jaw Jaw

Blueprint



Technical data

Part Code	WLL ton	Thread	A mm	B mm	C mm	E mm	F mm	G mm	M mm	N mm	L mm	Weight (kg)
422100050740	0.54	M10	9.65	12.7	152	410	258	22.1	441	289	8	0.37
422100100740	1	M12	12.7	16	152	470	292	26.9	508	330	10	0.71
422100160745	1.59	M16	16	19	200	509	340	33.3	562	378	12.7	1.23
422100160740	1.59	M16	16	19	229	662	401	33.3	715	454	12.7	1.56
422100240740	2.36	M20	19.1	23.4	305	851	508	38.1	917	574	16	2.98
422100330740	3.27	M22	22.4	28.7	375	892	543	44.5	967	618	19	3.71
422100450740	4.54	M25	25.4	30	305	933	577	52.5	1,018	662	22.5	5.53
422100690740	6.89	M32	31.8	44.5	305	1,012	644	71.5	1,119	750	29	9.36
422100970740	9.71	M38	38.1	52	305	1,054	673	71.5	1,181	800	35	13.9
422101270740	12.7	M45	44.5	50	457	1,356	899	86	1,503	1,046	41	24.5
422102720740	27.2	M64	63.5	73	610	1,854	1,244	113	2,087	1,478	57	75
422104280740	42.8	M51	51	63.5	610	1,766	1,157	93.5	1,949	1,339	50.5	16.8