Lifting Solutions Group
Axel Johnson International

Rigging Screw Grade S Eye/Jaw

Product information

Generally used for straight or in line tensioning in conjunction with wire rope and or chain assemblies when heavy duty straining and lifting applications are required
... *Read more*



Finish: hot dipped galvanised

Safety factor: 6:1
Grade: 6

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Rigging Screw Grade S Eye/Jaw

Blueprint



Technical data

Part Code	WLL ton	A mm	D mm	E mm	F mm	G mm	H mm	I mm	C1 mm	C2 mm	J mm	N mm	O mm	Weight (kg)
422100120750	1.2	229	25	19	11	14	36	36	183	182	10	353	529	0.98
422100200750	2	229	27	22	14	18	46	40	194	194	12.7	393	539	1.4
422100320750	3.2	229	34	22	16	22	54	50	204	223	16	420	560	2.1
422100500750	5	356	42	32	19	25	63	51	292	292	22	566	826	4.85
422101000750	10	381	51	38	25	34	84	64	320	320	25	635	870	8.08
422101200750	12	407	55	50	32	37	92	74	356	356	27	695	1,010	10.75

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved